


BAW M30ME-UAC10B-S04G
Inductive Distance Sensors

2...10 mm
0...10 V



PX0326a

Electrical data:

Connection	connector
Rated operational voltage DC	24 V
Rated insulation voltage (Ui)	250 AC
Electrical type	DC
No-load supply current I _o at I _e	10 mA
Supply voltage ripple	15 %
Switching element function	0...10 V
Supply voltage max. (U _b)	30 V
Supply voltage min. (U _b)	15 V
Output voltage s _I max	10 V
Output voltage s _I min	0 V
Cutoff frequency (-3dB output amplitude)	500 Hz
Load resistance min (R _L)	2000 Ohm
Output voltage at se	5 V
Temperature compensation	no
Linear range max (s _I)	2 mm
Linear range min (s _I)	10 mm
Non-linearity	±240 µm
Output signal	0...10 V


General data:

Supply voltage indicator	no
Degree of protection IP	IP 67 acc. BWN Pr 14
Insulation class	2
Recommended connector	BKS-_19/BKS-_20
Polarity reversal resistant	yes
Protected against reversal	yes

Mechanical data:

Midpoint of linear range (se)	6 mm
Connection type	M12x1-S04
Mounting	flush mountable
Surface treatment	nickel plated
Ambient temperature max (T _a)	70 °C
Ambient temperature min (T _a)	-10 °C
Sensing face material	PBT
Housing material	CuZn
Repeatability	3 %
Working area max (s _a)	10 mm
Working area min (s _a)	2 mm
Time delay before available max	1,5 ms
Measurement velocity	20 m/s
Opt. working temperature max.	50 °C
Opt. working temperature min.	10 °C
Temperature coefficient max.	5,0 µm/K
Temperature coefficient min.	-1,0 µm/K
Temperature coefficient typ.	1,5 µm/K
Repeat accuracy	±10,0 µm
Adjustment indicator	yes
Working range	2...10 mm

Wiring:



Pinout:

