


BES 515-123-S 4-C
BES02E1

PNP
NO/NC
non flush mountable



Electrical data:

Connection	Connector S4 (M12)
Electrical type	DC
No-load supply current damped	= 30 mA
Switching element function	NO/NC
Operating frequency (f)	200 Hz
Time delay before availability	10 ms
Voltage drop max. static	2,5 V
Utilization category	DC 13
Off-state current max (I _r)	80 µA
Ripple max. of U _e	= 15 %
Supply voltage max. (U _b)	30 V
Rated operational voltage (U _e)	24 DC V
Load current capacity (I _e)	200 mA
Hysteresis max (H)	15 %
Switching output	PNP
Supply voltage min. (U _b)	10 V


Mechanical data:

Number of Wires	4-wire
Repeat accuracy max. (R)	5 %
Mounting	non flush mountable
Sensing face material	PA 12
Housing material	1.4305
Ambient temperature max	+85 °C
Rated operating distance (sn)	8 mm
Diameter	M18x1 mm
Assured operating distance	0...6,5 mm
Ambient temperature min	-40 °C
Degree of pollution	3

General data:

Insulation class	2
Output indication	yes
Short circuit protected	yes
Protected against polarity reversal	yes
Brand	Proxinox
Approval	CE, ULZ1
Degree of protection IP	IP68 per BWN Pr 20

Wiring:



Pinout:

