


BES 515-326-E5-T-S 4
BES02ET

PNP
NO
flush mountable



PX0580

Electrical data:

Time delay before availability	15 ms
Hysteresis max (H)	15 %
Switching element function	NO
Operating frequency (f)	500 Hz
Supply voltage min. (Ub)	10 V
Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	130 mA
Electrical type	DC
Off-state current max (Ir)	80 µA
Ripple max. of Ue	= 15 %
Supply voltage max. (Ub)	30 V
Connection	Connector S4 (M12)
Utilization category	DC 13
No-load supply current damped	= 25 mA
Switching output	PNP
Voltage drop max. static	3,5 V


Mechanical data:

Number of Wires	3-wire
Ambient temperature min	-40 °C
Degree of pollution	3
Sensing face material	PA 12
Housing material	1.4571
Rated operating distance (sn)	5 mm
Diameter	M18x1 mm
Assured operating distance	0...4,0 mm
Mounting	flush mountable
Ambient temperature max	+105 °C
Repeat accuracy max. (R)	5 %

General data:

Short circuit protected	yes
Protected against polarity reversal	yes
Degree of protection IP	IP69K ; IP68 per BWN Pr 27
Brand	Proxinox
Approval	CE,ULZ1

Wiring:



Pinout:

