


BES 516-300-S170-S49
BES0184

NPN
NO
flush mountable



Electrical data:

Rated operational voltage (U _e)	24 DC V
Load current capacity (I _e)	200 mA
Utilization category	DC 13
Hysteresis max (H)	15 %
Switching output	NPN
Supply voltage max. (U _b)	30 V
Time delay before availability	10 ms
Switching element function	NO
No-load supply current damped	= 15 mA
No-load supply current undamped	4 mA
Operating frequency (f)	5000 Hz
Voltage drop max. static	2,5 V
Connection	Connector S49 (M8)
Electrical type	DC
Off-state current max (I _r)	80 µA
Ripple max. of U _e	= 15 %
Supply voltage min. (U _b)	10 V


Mechanical data:

Mounting	flush mountable
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Degree of pollution	3
Sensing face material	POM
Number of Wires	3-wire
Assured operating distance	0...1,2 mm
Repeat accuracy max. (R)	5 %
Rated operating distance (s _n)	1,5 mm
Housing material	Gd Zn Al

General data:

Degree of protection IP	IP67
Approval	CE, c_ul_us
Output indication	yes
Short circuit protected	yes
Protected against polarity reversal	yes

Wiring:



Pinout:

