


BES 516-3021-G-E5-C-S49
BES00KY

PNP
NC
flush mountable



Electrical data:

Off-state current max (I _r)	20 µA
Ripple max. of U _e	= 15 %
Supply voltage max. (U _b)	30 V
Connection	Connector S49 (M8)
Electrical type	DC
No-load supply current damped	3 mA
No-load supply current undamped	9 mA
Operating frequency (f)	1500 Hz
Voltage drop max. static	2,5 V
Rated operational voltage (U _e)	24 DC V
Load current capacity (I _e)	200 mA
Switching element function	NC
Time delay before availability	20 ms
Utilization category	DC 13
Hysteresis max (H)	1...15 %
Switching output	PNP
Supply voltage min. (U _b)	10 V

Mechanical data:

Assured operating distance	0...1,6 mm
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Number of Wires	3-wire
Mounting	flush mountable
Degree of pollution	3
Diameter	6,5 mm
Repeat accuracy max. (R)	5 %
Rated operating distance (sn)	2 mm
Sensing face material	PA 12
Housing material	corrosion resistance Steel

General data:

Degree of protection IP	IP67
Approval	CE,c_ul_us
Output indication	yes
Short circuit protected	yes
Protected against polarity reversal	yes

Wiring:



Pinout:

