


BES 516-3028-E5-Y-S 4
BES00LM

PNP
NC
flush mountable



PX0326a

Electrical data:

Time delay before availability	10 ms
Utilization category	DC 13
Hysteresis max (H)	15 %
Switching output	PNP
Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	130 mA
Operating frequency (f)	200 Hz
Voltage drop max. static	3,5 V
Connection	Connector S4 (M12)
Electrical type	DC
Off-state current max (Ir)	80 µA
Ripple max. of Ue	= 15 %
Supply voltage max. (Ub)	30 V
Supply voltage min. (Ub)	10 V
No-load supply current damped	= 12 mA
Switching element function	NC

Mechanical data:

Diameter	M30x1.5 mm
Ambient temperature max	+70 °C
Number of Wires	3-wire
Mounting	flush mountable
Sensing face material	PA 12
Housing material	CuZn, nickel plated
Rated operating distance (sn)	10 mm
Repeat accuracy max. (R)	5 %
Assured operating distance	0...8,0 mm
Ambient temperature min	-25 °C
Degree of pollution	3

General data:

Degree of protection IP	IP67
Output indication	yes
Short circuit protected	yes
Protected against polarity reversal	yes
Approval	CE, ULZ1

Wiring:



Pinout:

