


BES 516-324-E4-C-02
BES00MY

PNP
NO
flush mountable



Electrical data:

Connection	Cable
Utilization category	DC 13
Hysteresis max (H)	15 %
Ripple max. of Ue	= 15 %
Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	200 mA
Electrical type	DC
Switching output	PNP
Switching element function	NO
Time delay before availability	20 ms
No-load supply current damped	9 mA
Off-state current max (Ir)	20 µA
Supply voltage max. (Ub)	30 V
Supply voltage min. (Ub)	10 V
Load capacitance max	0,5 µF
Operating frequency (f)	3000 Hz
Voltage drop max. static	2,5 V

Mechanical data:

Diameter	M8x1 mm
Cable code designation	LiYY-O
Ambient temperature max	+70 °C
Repeat accuracy max. (R)	5 %
Number of wires	3-wire
Assured operating distance	0...1,2 mm
Mounting	flush mountable
Sensing face material	PA 12
Housing material	corrosion resistance Steel
Rated operating distance (sn)	1,5 mm
Ambient temperature min	-25 °C
Degree of pollution	3

General data:

Output indication	yes
Approval	CE,c_ul_us
Short circuit protected	yes
Degree of protection IP	IP68 per BWN Pr 20
Insulation class	2
Protected against polarity reversal	yes

Wiring:

