


BES 516-324-SA 33

PNP
NO
flush mountable



PX0049

Electrical data:

Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	200 mA
Operating frequency (f)	1000 Hz
Voltage drop max. static	2,5 V
Off-state current max (Ir)	80 µA
Ripple max. of Ue	= 15 %
Supply voltage max. (Ub)	30 V
Supply voltage min. (Ub)	10 V
Connection	Connector S49 (M8)
Electrical type	DC
No-load supply current damped	= 25 mA
Switching element function	NO
Time delay before availability	10 ms
Utilization category	DC 13
Hysteresis max (H)	15 %
Switching output	PNP

Mechanical data:

Number of Wires	3-wire
Mounting	flush mountable
Sensing face material	PBTB
Rated operating distance (sn)	1,5 mm
Ambient temperature max	+70 °C
Diameter	M8x1 mm
Housing material	corrosion resistance Steel
Repeat accuracy max. (R)	5 %
Assured operating distance	0...1,2 mm
Ambient temperature min	-25 °C
Degree of pollution	3

General data:

Output indication	yes
Short circuit protected	yes
Protected against polarity reversal	yes
Degree of protection IP	IP67
Approval	CE,c_ul_us

Wiring:

