


BES 516-343-EO-C-PU-03
BES01F2

NPN
NO
flush mountable



PX2010

Electrical data:

Connection	Cable
Rated operational voltage (Ue)	24 DC V
Utilization category	DC 13
Off-state current max (I _r)	20 µA
Ripple max. of Ue	= 15 %
Load current capacity (I _e)	200 mA
Hysteresis max (H)	15 %
Supply voltage max. (U _b)	30 V
Supply voltage min. (U _b)	10 V
Electrical type	DC
Switching output	NPN
Switching element function	NO
Time delay before availability	20 ms
No-load supply current damped	= 11 mA
No-load supply current undamped	3 mA
Operating frequency (f)	3000 Hz
Voltage drop max. static	2,5 V

Mechanical data:

Mounting	flush mountable
Ambient temperature min	-25 °C
Degree of pollution	3
Number of wires	3-wire
Assured operating distance	0...1,2 mm
Cable code designation	LifY-Y-11Y-O
Ambient temperature max	+70 °C
Repeat accuracy max. (R)	5 %
Rated operating distance (sn)	1,5 mm
Diameter	M8x1 mm
Sensing face material	PA 12
Housing material	corrosion resistance Steel

General data:

Degree of protection IP	IP68 per BWN Pr 20
Protected against polarity reversal	yes
Output indication	yes
Short circuit protected	yes
Approval	CE,c_ul_us

Wiring:

