


BES 516-367-E5-Y-S 4
BES00YC

PNP
NC
flush mountable



PX0453a

Electrical data:

Connection	Connector S4 (M12)
Electrical type	DC
No-load supply current damped	= 8 mA
Operating frequency (f)	500 Hz
Voltage drop max. static	3,5 V
Time delay before availability	10 ms
Switching element function	NC
Load current capacity (I _e)	130 mA
Off-state current max (I _r)	80 µA
Ripple max. of U _e	= 15 %
Supply voltage max. (U _b)	30 V
Supply voltage min. (U _b)	10 V
Rated operational voltage (U _e)	24 DC V
Utilization category	DC 13
Hysteresis max (H)	15 %
Switching output	PNP

Mechanical data:

Number of Wires	3-wire
Assured operating distance	0...4,0 mm
Sensing face material	PA 12
Mounting	flush mountable
Ambient temperature max	+70 °C
Rated operating distance (sn)	5 mm
Housing material	CuZn, nickel plated
Repeat accuracy max. (R)	5 %
Diameter	M18x1 mm
Ambient temperature min	-25 °C
Degree of pollution	3

General data:

Output indication	yes
Short circuit protected	yes
Protected against polarity reversal	yes
Degree of protection IP	IP67
Approval	CE

Wiring:



Pinout:

