


BES 516-371-E5-C-S49
BES00ZC

PNP
NO
flush mountable



Electrical data:

Connection	Connector S49 (M8)
Electrical type	DC
No-load supply current damped	9 mA
No-load supply current undamped	3 mA
Operating frequency (f)	3000 Hz
Voltage drop max. static	2,5 V
Time delay before availability	20 ms
Switching element function	NO
Load current capacity (I _e)	200 mA
Off-state current max (I _r)	20 µA
Ripple max. of U _e	= 15 %
Supply voltage max. (U _b)	30 V
Supply voltage min. (U _b)	10 V
Rated operational voltage (U _e)	24 DC V
Utilization category	DC 13
Hysteresis max (H)	15 %
Switching output	PNP


Mechanical data:

Number of Wires	3-wire
Mounting	flush mountable
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Assured operating distance	0...1,2 mm
Housing material	corrosion resistance Steel
Repeat accuracy max. (R)	5 %
Rated operating distance (sn)	1,5 mm
Sensing face material	PA 12
Diameter	6,5 mm
Degree of pollution	3

General data:

Degree of protection IP	IP67
Output indication	yes
Short circuit protected	yes
Protected against polarity reversal	yes
Approval	CE,c_ul_us

Wiring:



Pinout:

