


BES 516-377-E4-C-02
BES010T

PNP
NC
flush mountable



Electrical data:

Time delay before availability	20 ms
Hysteresis max (H)	15 %
Load capacitance max	0,5 μ F
Operating frequency (f)	3000 Hz
Voltage drop max. static	2,5 V
Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	200 mA
Utilization category	DC 13
Switching output	PNP
Switching element function	NC
No-load supply current damped	3 mA
Supply voltage max. (Ub)	30 V
Supply voltage min. (Ub)	10 V
Connection	Cable
Electrical type	DC
Off-state current max (Ir)	20 μ A
Ripple max. of Ue	= 15 %

Mechanical data:

Tightening torque	5 Nm
Rated operating distance (sn)	1,5 mm
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Degree of pollution	3
Number of wires	3-wire
Mounting	flush mountable
Repeat accuracy max. (R)	5 %
Sensing face material	PA 12
Housing material	corrosion resistance Steel
Diameter	M8x1 mm
Assured operating distance	0...1,2 mm
Cable code designation	LiYY-O

General data:

Approval	CE,c_ul_us
Insulation class	2
Protected against polarity reversal	yes
Output indication	yes
Short circuit protected	yes
Degree of protection IP	IP68 per BWN Pr 20

Wiring:

