


BES 516-377-G-S49-C
BES01LP

PNP
NC
flush mountable



PX2012

Electrical data:

Connection	Connector S49 (M8)
Electrical type	DC
No-load supply current damped	3 mA
Operating frequency (f)	1500 Hz
Load current capacity (I _e)	200 mA
No-load supply current undamped	9 mA
Off-state current max (I _r)	20 µA
Voltage drop max. static	2,5 V
Supply voltage max. (U _b)	30 V
Rated operational voltage (U _e)	24 DC V
Utilization category	DC 13
Ripple max. of U _e	= 15 %
Supply voltage min. (U _b)	10 V
Time delay before availability	20 ms
Hysteresis max (H)	15 %
Switching output	PNP
Switching element function	NC

Mechanical data:

Number of Wires	3-wire
Degree of pollution	3
Sensing face material	PBT
Rated operating distance (s _n)	2 mm
Assured operating distance	0...1,6 mm
Ambient temperature max	+70 °C
Mounting	flush mountable
Ambient temperature min	-25 °C
Diameter	M8x1 mm
Housing material	corrosion resistance Steel
Repeat accuracy max. (R)	5 %

General data:

Output indication	yes
Protected against polarity reversal	yes
Degree of protection IP	IP68 per BWN Pr 20
Short circuit protected	yes
Approval	CE,c_ul_us
Insulation class	2

Wiring:



Pinout:

