


BES 516-383-EO-C-02
BES01M0

PNP
NO
non flush mountable



Electrical data:

Utilization category	DC 13
Off-state current max. (Ir)	20 μ A
Ripple max. of Ue	= 15 %
Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	200 mA
Hysteresis max. (H)	15 %
No-load supply current undamped	3 mA
Supply voltage max. (Ub)	30 V
Supply voltage min. (Ub)	10 V
Time delay before availability	20 ms
No-load supply current damped	9 mA
Operating frequency (f)	2000 Hz
Voltage drop max. static	2,5 V
Connection	Cable
Electrical type	DC
Switching output	PNP
Switching element function	NO

General data:

Degree of protection IP	IP68 per BWN Pr 20
Insulation class	2
Protected against polarity reversal	yes
Output indication	yes
Short circuit protected	yes
Approval	CE,c_ul_us

Wiring:



Mechanical data:

Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Degree of pollution	3
Rated operating distance (sn)	2,5 mm
Assured operating distance	0...2,0 mm
Cable code designation	LiYY-O
Repeat accuracy max. (R)	5 %
Number of wires	3-wire
Mounting	non flush mountable
Diameter	M8x1 mm
Sensing face material	PA 12
Housing material	corrosion resistance Steel