


BES G06ED-PSC40F-BP02
BES000E

PNP
NO
non flush mountable



Electrical data:

Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	200 mA
Output resistance (Ra)	33 + D kOhm
Utilization category	DC 13
Load capacitance max	0,5 µF
No-load supply current damped	10 mA
Switching output	PNP
Switching element function	NO
Rated insulation voltage (Ui)	250 AC
Time delay before availability	20 ms
Hysteresis max (H)	15 %
Ripple max. of Ue	15 %
Supply voltage max. (Ub)	30 V
Supply voltage min. (Ub)	10 V
Connection	Cable
Electrical type	DC
No-load supply current undamped	3 mA
Off-state current max (Ir)	10 µA
Operating frequency (f)	1500 Hz
Voltage drop max. static	2,5 V

Mechanical data:

Conductor cross section	3x0,14
Housing material	corrosion resistance Steel
Rated operating distance (sn)	4 mm
Diameter	6,5 mm
Cable length	2 m
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Repeat accuracy max. (R)	5 %
Number of wires	3-wire
Assured operating distance	0...3,2 mm
Cable code designation	PUR
Mounting	non flush mountable
Degree of pollution	3
Sensing face material	PA 12

General data:

Output indication	yes
Short circuit protected	yes
Protected against polarity reversal	yes
Approval	CE,c_ul_us
Degree of protection IP	IP68 per BWN Pr 20
Insulation class	2
Brand	GlobalProx

Wiring:

