


BES M05ED-POC50F-EP05
BES0138

PNP
NC
non flush mountable



Electrical data:

Connection	Cable
Electrical type	DC
Ripple max. of Ue	10 %
Switching output	PNP
Supply voltage max. (Ub)	30 V
Supply voltage min. (Ub)	10 V
Time delay before availability	20 ms
No-load supply current damped	10 mA
Operating frequency (f)	3000 Hz
Voltage drop max. static	2,5 V
Utilization category	DC 13
Off-state current max (Ir)	10 µA
Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	100 mA
Hysteresis max (H)	20 %
Switching element function	NC

Mechanical data:

Number of wires	3-wire
Sensing face material	POM
Housing material	corrosion resistance Steel
Diameter	M5 mm
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Degree of pollution	3
Repeat accuracy max. (R)	10 %
Tightening torque	1 Nm
Rated operating distance (sn)	5 mm
Assured operating distance	0...4,1 mm
Cable code designation	LifY-11Y-0, 3x0,14mm²
Mounting	non flush mountable

General data:

Short circuit protected	yes
Approval	CE,c_ul_us
Degree of protection IP	IP67
Protected against polarity reversal	yes

Wiring:

