


BES M08MG-USC20B-BP03
BES001P

non polarized
NO
flush mountable



Electrical data:

Ripple of power supply	15 %
Switching output	non polarized
Switching element function	NO
Operating frequency (f)	1500 Hz
Voltage drop static max	5 V
Supply voltage max DC (UB)	36 V
Supply voltage min DC (UB)	10 V
Connection	Cable
Rated operational voltage DC	24 DC V
Rated operational current (Ie)	100 mA
Time delay before availability	50 ms
Electrical type	DC
Utilization category	DC 13
Hysteresis max (H)	20 %
Minimum operating current (Im)	5 mA
Off-state current max (Ir)	600 µA

Mechanical data:

Assured operating distance	0...1,6 mm
Mounting	flush mountable
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Degree of pollution	3
Number of wires	2-wire
Tightening torque	03. Jun Nm
Rated operating distance (sn)	2 mm
Diameter	M 8x1 mm
Sensing face material	PBT
Housing material	CuZn, Ni free coated
Repeat accuracy max. (R)	5 %

General data:

Power Indication	no
Output indication	yes
Short circuit protected	yes
Brand	GlobalProx
Degree of protection IP	IP67
Protected against polarity reversal	yes
Approval	CE

Wiring:

