


BES M12MF1-PSC70F-S04G
BES02WT

PNP
NO
non flush mountable



Electrical data:

Rated operational voltage (Ue)	24 DC V
Utilization category	DC 13
Hysteresis max (H)	10 %
Supply voltage min. (Ub)	10 V
Load current capacity (Ie)	200 mA
Off-state current max (Ir)	100 µA
Supply voltage max. (Ub)	30 V
Switching output	PNP
Switching element function	NO
Connection	Connector S4 (M12)
Electrical type	DC
No-load supply current damped	= 10 mA
No-load supply current undamped	10 mA
Operating frequency (f)	400 Hz
Voltage drop max. static	2 V

Mechanical data:

Mounting	non flush mountable
Sensing face material	PBTP
Tightening torque	10 Nm
Rated operating distance (sn)	7 mm
Assured operating distance	0...5,6 mm
Housing material	CuZn, chrome plated
Repeat accuracy max. (R)	5 %
Diameter	M12x1 mm
Ambient temperature max	+70 °C
Number of Wires	3-wire
Ambient temperature min	-25 °C

General data:

Output indication	yes
Brand	SuperG
Degree of protection IP	IP67
Short circuit protected	yes
Approval	CE
Protected against polarity reversal	yes

Wiring:



Pinout:

