


BES M12MI-NSC40B-BV03
BES0057

NPN
NO
flush mountable



Electrical data:

Connection	Cable
Utilization category	DC 13
Switching output	NPN
Switching element function	NO
Electrical type	DC
No-load supply current undamped	15 mA
Off-state current max (I _r)	20 µA
Supply voltage max. (U _b)	30 V
Supply voltage min. (U _b)	12 V
Rated operational voltage (U _e)	24 DC V
Load current capacity (I _e)	200 mA
Hysteresis max (H)	15 %
Ripple max. of U _e	= 15 %
Time delay before availability	10 ms
No-load supply current damped	= 15 mA
Operating frequency (f)	300 Hz
Voltage drop max. static	2,5 V

Mechanical data:

Number of wires	3-wire
Assured operating distance	0...3,2 mm
Cable code designation	LiYY-O
Repeat accuracy max. (R)	5 %
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Tightening torque	10 Nm
Mounting	flush mountable
Degree of pollution	3
Sensing face material	LCP
Housing material	CuZn, nickel plated
Rated operating distance (sn)	4 mm
Diameter	M12x1 mm

General data:

Approval	CE,c_ul_us
Insulation class	2
Protected against polarity reversal	yes
Brand	GlobalProx
Degree of protection IP	IP68 per BWN Pr 20
Output indication	yes
Short circuit protected	yes

Wiring:

