


BES M18MF1-PSC50A-S04G-W
BES02K9

PNP
NO
flush mountable



PX1755

Electrical data:

Rated operational voltage (Ue)	24 DC V
Utilization category	DC 13
Hysteresis max (H)	15 %
Ripple max. of Ue	= 10 %
Supply voltage min. (Ub)	10 V
Load current capacity (Ie)	200 mA
Off-state current max (Ir)	80 µA
Supply voltage max. (Ub)	30 V
Time delay before availability	15 ms
Switching output	PNP
Switching element function	NO
Connection	Connector S4 (M12)
Electrical type	DC
No-load supply current damped	= 15 mA
Operating frequency (f)	2500 Hz
Voltage drop max. static	2,5 V

Mechanical data:

Diameter	M18x1 mm
Housing material	CuZn, PTFE coated
Repeat accuracy max. (R)	5 %
Rated operating distance (sn)	5 mm
Assured operating distance	0...4,0 mm
Ambient temperature max	+70 °C
Mounting	flush mountable
Ambient temperature min	-25 °C
Number of Wires	3-wire
Degree of pollution	3
Sensing face material	LCP + PTFE

General data:

Short circuit protected	yes
Approval	CE, c_ul_us
Degree of protection IP	IP67
Features	Factor 1
Output indication	yes
Protected against polarity reversal	yes

Wiring:



Pinout:

