


BES M30MI1-POC22B-S04G
BES02YL

PNP
NC
quasi flush mountable



Electrical data:

Load current capacity (I _e)	200 mA
Off-state current max (I _r)	100 µA
Supply voltage max. (U _b)	30 V
Rated operational voltage (U _e)	24 DC V
Utilization category	DC 13
Hysteresis max (H)	10 %
Ripple max. of U _e	= 20 %
Supply voltage min. (U _b)	10 V
Connection	Connector S4 (M12)
Electrical type	DC
No-load supply current damped	= 10 mA
No-load supply current undamped	10 mA
Operating frequency (f)	200 Hz
Voltage drop max. static	2 V
Time delay before availability	200 ms
Switching output	PNP
Switching element function	NC

Mechanical data:

Ambient temperature min	-25 °C
Tightening torque	70 Nm
Rated operating distance (s _n)	22 mm
Assured operating distance	0...17,6 mm
Housing material	CuZn, chrome plated
Repeat accuracy max. (R)	5 %
Number of Wires	3-wire
Mounting	quasi flush mountable
Degree of pollution	3
Sensing face material	PBT
Diameter	M30x1.5 mm
Ambient temperature max	+70 °C

General data:

Short circuit protected	yes
Approval	CE
Output indication	yes
Protected against polarity reversal	yes
Degree of protection IP	IP67

Wiring:



Pinout:

