


BES M30MI-POC15B-S04K
BES009U

PNP
NC
flush mountable



Electrical data:

Load current capacity (I _e)	200 mA
No-load supply current undamped	10 mA
Off-state current max. (I _r)	10 µA
Supply voltage max. (U _b)	30 V
Connection	Connector S4 (M12)
Electrical type	DC
No-load supply current damped	5 mA
Operating frequency (f)	100 Hz
Voltage drop max. static	2,5 V
Time delay before availability	15 ms
Hysteresis max (H)	15 %
Load capacitance max	0,5 µF
Switching output	PNP
Switching element function	NC
Supply voltage min. (U _b)	10 V
Rated operational voltage (U _e)	24 DC V
Utilization category	DC 13
Ripple max. of U _e	= 15 %

Mechanical data:

Tightening torque	70 Nm
Rated operating distance (s _n)	15 mm
Assured operating distance	0...12,2 mm
Housing material	CuZn, Ni free coated
Repeat accuracy max. (R)	5 %
Number of Wires	3-wire
Degree of pollution	3
Sensing face material	PA 12
Mounting	flush mountable
Ambient temperature max	+70 °C
Diameter	M30x1.5 mm
Ambient temperature min	-25 °C

General data:

Short circuit protected	yes
Approval	CE,c_ul_us
Output indication	yes
Protected against polarity reversal	yes
Insulation class	2
Brand	GlobalProx
Degree of protection IP	IP67

Wiring:



Pinout:

