


BES M30MM-NSC30F-BV02
BES00AN

NPN
NO
non flush mountable



Electrical data:

Connection	Cable
Electrical type	DC
No-load supply current undamped	3 mA
Off-state current max (I _r)	10 µA
Supply voltage max. (U _b)	30 V
Supply voltage min. (U _b)	10 V
Rated operational voltage (U _e)	24 DC V
Load current capacity (I _e)	200 mA
No-load supply current damped	14 mA
Operating frequency (f)	300 Hz
Voltage drop max. static	2.5 V
Time delay before availability	20 ms
Hysteresis max (H)	20 %
Ripple max. of U _e	= 15 %
Utilization category	DC 13
Switching output	NPN
Switching element function	NO

Mechanical data:

Rated operating distance (sn)	30 mm
Diameter	M30x1.5 mm
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Degree of pollution	3
Sensing face material	PBT
Tightening torque	70 Nm
Mounting	non flush mountable
Housing material	CuZn, Ni free coated
Number of wires	3-wire
Assured operating distance	0...24 mm
Cable code designation	LifYY-0
Repeat accuracy max. (R)	5 %

General data:

Brand	GlobalProx
Degree of protection IP	IP67
Insulation class	2
Output indication	yes
Short circuit protected	yes
Protected against polarity reversal	yes
Approval	CE,c_ul_us

Wiring:

