


BES R01ZC-PAC70B-BP00.5-GS04

Inductive Sensors

PNP NO/NC
flush mountable
Sn = 7 mm

**Electrical data:**


Connection	cable with connector
Load current capacity (I _e)	200 mA
Electrical type	DC
Utilization category	DC 13
Hysteresis max (H)	15 %
No-load supply current damped	15 mA
Off-state current max (I _r)	80 µA
Ripple max. of U _e	10 %
Switching output	PNP
Switching element function	NO/NC
Operating frequency (f)	150 Hz
Voltage drop max. static	2,5 V
Supply voltage max. (U _b)	30 V
Supply voltage min. (U _b)	10 V

Mechanical data:

Rated operating distance (s _n)	7 mm
Assured operating distance	0...5,6 mm
Cable code designation	4x0,14mm ²
Mounting	flush mountable
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Degree of pollution	3
Sensing face material	PA 12
Housing material	GD Zn
Repeat accuracy max. (R)	= 5 %

General data:

Power Indication	yes
Output indication	yes
Short circuit protected	yes
Degree of protection IP	IP67
Protected against polarity reversal	yes
Approval	CE,c_ul_us

wiring**Pinout**