


BHS B400V-PSD15-S04
BHS0063

PNP
NO
flush mountable




Electrical data:

Connection	Connector S4 (M12)
Electrical type	DC
No-load supply current damped	8 mA
Operating frequency (f)	400 Hz
Load current capacity (I _e)	200 mA
Off-state current max (I _r)	10 µA
Voltage drop max. static	2,5 V
Supply voltage max. (U _b)	30 V
Rated operational voltage (U _e)	24 DC V
Utilization category	DC 13
Ripple max. of U _e	15 %
Supply voltage min. (U _b)	10 V
Time delay before availability	20 ms
Hysteresis max (H)	15 %
Load capacitance max	0,5 µF
Switching output	PNP
Switching element function	NO

General data:

Power Indication	no
Degree of protection IP	IP68 per BWN Pr 20
Features	pressure rated to 500 bar
Short circuit protected	yes
Approval	CE
Output indication	no
Recommended connector	BKS-B 19-1-PU2
Protected against polarity reversal	yes

Wiring:



Pinout:



Mechanical data:

Mounting	flush mountable
Ambient temperature max	+120 °C
Tightening torque	25 Nm
Rated operating distance (sn)	1,5 mm
Assured operating distance	0...1,2 mm
Ambient temperature min	-25 °C
Degree of pollution	3
Sensing face material	Ceramic
Diameter	M12x1 mm
Temperature drift max.	15 %
Housing material	1.4104
Repeat accuracy max. (R)	5 %