



Inductive Proximity Switches


Output Schematics



Connector M8




Not to be
used for
Safety
Applications



SPECIFICATIONS

	Ø4 mm	Ø4 mm	M5x0.5	M5x0.5
Sensing Distance	1.5 mm - Shielded	1.5 mm - Shielded	0.8 mm - Shielded	0.8 mm - Shielded
Operating Voltage	10...30 VDC, 3-wire	10...30 VDC, 3-wire	10...30 VDC, 3-wire	10...30 VDC, 3-wire
Reverse Polarity Protection	built-in	built-in	built-in	built-in
Current Consumption	< 8 mA	< 8 mA	< 8 mA	< 8 mA
Current Load Capability	200 mA	200 mA	200 mA	200 mA
Short Circuit Protection	built-in - self resetting	built-in - self resetting	built-in - self resetting	built-in - self resetting
Voltage Drop	< 1.5 V @ 200 mA	< 1.5 V @ 200 mA	< 1.5 V @ 200 mA	< 1.5 V @ 200 mA
Switching Frequency	1000 Hz	1000 Hz	2000 Hz	2000 Hz
Repeatability	< 1 % (Sn)	< 1 % (Sn)	< 1 % (Sn)	< 1 % (Sn)
Hysteresis	3...15 %	3...15 %	3...15 %	3...15 %
Operating Temperature	-25...75 °C	-25...75 °C	-25...75 °C	-25...75 °C
Protection Class	IP67	IP67	IP67	IP67
Sensing Face Material	POM	POM	POM	POM
Housing Material	1.4305 / SS303	1.4305 / SS303	1.4305 / SS303	1.4305 / SS303
Connection	High-Flex PVC, 2m	Conn. M8, 3-pole, 30cm	High-Flex PVC, 2m	Conn. M8, 3-pole, 30cm
Output Indicator	Integrated	Integrated	Integrated	Integrated
Article Code				
PNP - NO, 3-wire	IPSD4-S1.5PO25/A2P	IPSD4-S1.5PO25/3P8	IPS5-S08PO25/A2P	IPS5-S08PO25/3P8
PNP - NC, 3-wire	IPSD4-S1.5PC25/A2P	IPSD4-S1.5PC25/3P8	IPS5-S08PC25/A2P	IPS5-S08PC25/3P8
NPN - NO, 3-wire	IPSD4-S1.5NO25/A2P	IPSD4-S1.5NO25/3P8	IPS5-S08NO25/A2P	IPS5-S08NO25/3P8
NPN - NC, 3-wire	IPSD4-S1.5NC25/A2P	IPSD4-S1.5NC25/3P8	IPS5-S08NC25/A2P	IPS5-S08NC25/3P8



M5x0.5	M5x0.5	M5x0.5	M5x0.5	5 x 5	5 x 5
0.8 mm - Shielded	1.5 mm - Shielded	1.5 mm - Shielded	1.5 mm - Shielded	0.8 mm - Shielded	0.8 mm - Shielded
10...30 VDC, 3-wire built-in < 8 mA 200 mA built-in - self resetting < 1.5 V @ 200 mA 2000 Hz < 1 % (Sn) 3...15 % -25...75 °C IP67 POM 1.4305 / SS303 Connector M8, 3-pole Integrated	10...30 VDC, 3-wire built-in < 8 mA 200 mA built-in - self resetting < 1.5 V @ 200 mA 1000 Hz < 1 % (Sn) 3...15 % -25...75 °C IP67 POM 1.4305 / SS303 High-Flex PVC, 2m Integrated	10...30 VDC, 3-wire built-in < 8 mA 200 mA built-in - self resetting < 1.5 V @ 200 mA 1000 Hz < 1 % (Sn) 3...15 % -25...75 °C IP67 POM 1.4305 / SS303 Conn. M8, 3-pole, 30cm Integrated	10...30 VDC, 3-wire built-in < 8 mA 200 mA built-in - self resetting < 1.5 V @ 200 mA 1000 Hz < 1 % (Sn) 3...15 % -25...75 °C IP67 POM 1.4305 / SS303 Connector M8, 3-pole Integrated	10...30 VDC, 3-wire built-in < 8 mA 200 mA built-in - self resetting < 1.5 V @ 200 mA 2000 Hz < 1 % (Sn) 3...15 % -25...75 °C IP67 POM Plated Brass High-Flex PVC, 2m Integrated	10...30 VDC, 3-wire built-in < 8 mA 200 mA built-in - self resetting < 1.5 V @ 200 mA 2000 Hz < 1 % (Sn) 3...15 % -25...75 °C IP67 POM Plated Brass Conn. M8, 3-pole, 30cm Integrated
IPS5-S08PO40/M8 IPS5-S08PC40/M8	IPS5-S1.5PO25/A2P IPS5-S1.5PC25/A2P	IPS5-S1.5PO25/3P8 IPS5-S1.5PC25/3P8	IPS5-S1.5PO40/M8 IPS5-S1.5PC40/M8	IPS5-S08PO26/A2P IPS5-S08PC 26/A2P	IPS5-S08PO26/3P8 IPS5-S08PC26/3P8
IPS5-S08NO40/M8 IPS5-S08NC40/M8	IPS5-S1.5NO25/A2P IPS5-S1.5NC25/A2P	IPS5-S1.5NO25/3P8 IPS5-S1.5NC25/3P8	IPS5-S1.5NO40/M8 IPS5-S1.5NC40/M8	IPS5-S08NO26/A2P IPS5-S08NC26/A2P	IPS5-S08NO26/3P8 IPS5-S08NC26/3P8

Subject to reasonable modifications due to technical advances.

Printed in Germany

Sensotronic AB • Tel. +46 44 200 800 • Fax +46 44 200 899 • info@sensotronic.se • http://www.sensotronic.se

SENSOTRONIK