


OGUFIX 051 P3K-TSSL

Fork Light Barrier

- Quick commissioning, no setting elements
- No risk of wrong adjustments
- Value for money
- Mountable side by side
- Light/dark switching
- Metal casing
- High protection class
- 3-years function guarantee* *according to our General Conditions of Export




Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments.

These instruments shall exclusively be used by qualified personnel.

Repair only by di-soric.



TECHNICAL INFORMATION	
Evaluation	+20°C, 24V DC digital
Size	70 x 80 x 10 mm (Dimensions)
Design	fork
Fork opening	50 mm
Emitted light	Red, clocked
Service voltage	10 ... 35 V DC
Transmitter / receiver	transmitter + receiver
Output	pnp, 200 mA, NO/NC, switchable
Sensitivity adjustment	no setting elements
Internal power consumption	< 30 mA
Voltage drop	2,8 V
Operating frequency	2.500 Hz
Resolution	Ø 1,0 mm
Switching hysteresis	< 0,25 mm
Reproducibility	0,04 mm
Ambient temperature	-10 ... +60 °C
Ambient light immunity	> 20 kLx
Protection class	IP 67
Casing material	die-cast zinc black lacquered finish
Connection	Connector, M8, 3-poled