
LLRV 51 M 500 N3K-TSSL

Laser Line Retroreflective Sensor


- Fan-shaped laser beam with auto-collimation principle
- Detection of smallest parts within the entire active zone
- Red light laser, clocked
- 4-turn potentiometer
- Robust metal casing





Safety instructions

Inproper use may result in hazardous radiation exposure. Pay attention to accident prevenetion rules and laser class. The instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments. These instruments shall exclusively be used by qualified personnel. Repair only by di-soric.



TECHNICAL INFORMATION	+20°C, 24V DC
Evaluation	digital
Size	50 x 40 x 15 mm (Dimensions)
Design	cuboid design
Emitted light	Red light laser, 670 nm, clocked
Operating distance	50 500 mm
Service voltage	10 35 V DC
Laser class	2 (EN 60825-1)
Output	npn, 200 mA, NO/NC, switchable
Sensitivity adjustment	potentiometer
Internal power consumption	< 30 mA
Operating frequency	750 Hz
Resolution	25 100 % covering of laser line
Ambient temperature	+5 +50 °C
Ambient light immunity	> 15 kLx
Protection class	IP 67
Casing material	die-cast zinc lacquered finish
Material	polymethyl methacrylate (Window)
Connection	Connector, M8, 3-poled

