

## SAC-3P-M12MR/ 3,0-PUR P

Order No.: 1442560



Sensor/Actuator cable, 3-position, PUR, halogen-free, Black-gray  
RAL 7021, Plug, angled M12, A-coded, on Free conductor end, Cable  
length: 3 m

### Commercial data

|                          |                                                                                                       |
|--------------------------|-------------------------------------------------------------------------------------------------------|
| EAN                      | <br>4 046356 535328 |
| Note                     | Made-to-order                                                                                         |
| Pack                     | 1                                                                                                     |
| Customs tariff           | 85444290                                                                                              |
| Catalog page information | Page 114 (NTK-2010)                                                                                   |

### Product notes

WEEE/RoHS-compliant since:  
2010-02-04



### Technical data

#### General data

|                       |                            |
|-----------------------|----------------------------|
| Rated current at 40°C | 4 A                        |
| Rated voltage         | 250 V                      |
| Number of positions   | 3                          |
| Volume resistance     | $\leq 5 \text{ m}\Omega$   |
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Length of cable       | 3 m                        |

|                                            |                                                      |
|--------------------------------------------|------------------------------------------------------|
| Stripping length of the free conductor end | 50 mm                                                |
| Ambient temperature (operation)            | -25 °C ... 90 °C (Male connector / female connector) |

**General characteristics**

|                             |                                             |
|-----------------------------|---------------------------------------------|
| Standards/regulations       | M12 connector IEC 61076-2-101               |
| Coding                      | A - standard                                |
| Surge voltage category      | II                                          |
| Pollution degree            | 3                                           |
| Degree of protection        | IP65/IP68/IP69K                             |
| Insertion/withdrawal cycles | ≥ 100                                       |
| Contact material            | CuSn                                        |
| Contact surface material    | Ni/Au                                       |
| Contact carrier material    | TPU GF                                      |
| Material of grip body       | TPU, hardly inflammable, self-extinguishing |
| Material, knurls            | Polyamide                                   |
| Status display              | No                                          |


**Conductor data**

|                                    |                                |
|------------------------------------|--------------------------------|
| Cable type                         | PUR halogen-free black         |
| Cable type (abbreviation)          | PUR                            |
| Cable abbreviation                 | Li9Y11Y                        |
| Conductor cross section            | 0.34 mm <sup>2</sup>           |
| AWG signal line                    | 22                             |
| Conductor structure signal line    | 42x 0.10 mm                    |
| Core diameter including insulation | 1.27 mm ±0.02 mm               |
| Thickness, insulation              | ≥ 0.21 mm (Core insulation)    |
|                                    | ≥ 0.76 mm (Outer cable sheath) |
| External cable diameter            | 4.40 mm                        |
| Wire colors                        | Brown, blue, black             |
| External sheath, color             | Black-gray RAL 7021            |
| Insulation resistance              | ≥ 100 GΩ*km                    |
| Conductor resistance               | ≤ 58 Ω/m                       |
| Nominal voltage, conductor         | 300 V                          |
| Test voltage, conductor            | 3000 V                         |
| Overall twist                      | 3 wires, twisted               |
| Outer sheath, material             | PUR                            |

|                                               |                                                                                                                        |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Material conductor insulation                 | PP                                                                                                                     |
| Conductor material                            | Bare Cu litz wires                                                                                                     |
| Cable weight                                  | 26 kg/km                                                                                                               |
| Smallest bending radius, movable installation | 44 mm                                                                                                                  |
| Number of bending cycles                      | 4000000                                                                                                                |
| Bending radius                                | 44 mm                                                                                                                  |
| Traversing path                               | 10 m                                                                                                                   |
| Traversing rate                               | 3 m/s                                                                                                                  |
| Acceleration                                  | 10 m/s <sup>2</sup>                                                                                                    |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)<br>-5 °C ... 80 °C (cable, flexible installation)                         |
| Special properties                            | Flexible cable conduit capable<br>Silicone-free<br>Free of substances which would hinder coating with paint or varnish |
| Flame resistance                              | in accordance with DIN UL-Style 20549                                                                                  |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815                                                                               |
| Resistance to oil                             | in accordance with DIN EN 60811-2-1                                                                                    |
| Other resistance                              | Highly resistant to acids, alkaline solutions and solvents<br>hydrolysis and microbe resistant                         |


## Drawings

### Dimensioned drawing




M12 x 1 male connector, angled

Circuit diagram



Contact assignment of the M12 plug

Schematic diagram



Pin assignment M12 plug, 3-pos., A-coded, view male side