

SACC-VB-4CON-M16/A

Order No.: 1452136

The illustration shows the 3-pos. version



Ventilstecker, 4-polig, Bauform A, ohne Schutzbeschaltung,
Schraubanschluss, Kabelverschraubung M16

Commercial data

EAN	 4 046356 536301
Pack	1
Customs tariff	85366990

Product notes

WEEE/RoHS-compliant since:
2009-12-21



Technical data

General data


Rated current at 40°C	10 A
Rated voltage	230 V
Number of positions	4
Volume resistance	$\leq 4 \text{ M}\Omega$
Insulation resistance	$> 2 \text{ G}\Omega$

General characteristics

Standards/regulations	Valve connector EN 175301-803
Surge voltage category	II
Pollution degree	3
Degree of protection	IP65
Torque	1.8 Nm $\pm$ 0,2 (Pressure screw)
	0.4 Nm $\pm$ 0,4 (Zentralschraube)
	0.2 Nm $\pm$ 0.1 (Kontaktschraube)
Contact material	CuZn
Contact surface material	CuSn
Material, housing, valve plug	PA
Sealing material	NBR
Type of connection	Screw connection
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	16
External cable diameter	6 mm ... 8 mm

Drawings

Dimensioned drawing



Circuit diagram

