

SAC-3P-M12MR/A-1L-S

Order No.: 1505261



Valve connector type A, PE bridged, 18 mm contact spacing,
horizontal M12 connector

Commercial data

EAN	 4 017918 857035
Pack	5
Customs tariff	85366990
Catalog page information	Page 108 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
2006-10-31



Technical data

General data


Rated current at 40°C	4 A
Rated voltage	24 V AC/DC
Number of positions	3
Volume resistance	≤ 15 mΩ
Insulation resistance	≥ 100 MΩ
Ambient temperature (operation)	-25 °C ... 85 °C (valve plug)

General characteristics

Standards/regulations	M12 connector IEC 61076-2-101
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Insertion/withdrawal cycles	≥ 100
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ag
Valve plug contact insert material	PBT
Material, housing, valve plug	PBT
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	TPU
Type of connection	M12 male connector
Status display	Yellow LED
Protective circuit/component	Z diode


Drawings

Dimensioned drawing




Valve connector, type A with horizontal M12 connector


Circuit diagram



Schematic diagram



Pin assignment M12 plug, 3-pos., A-coded, view male side



Valve connector pin assignment, type A