

SACC-M12MS-4CON-PG11-DUO-M

Order No.: 1507052



Sensor/actuator connector, male, straight, 4-pos., M12, A-coded,
screw connection, metal knurl, cable screw connection Pg11-DUO

Commercial data

EAN	 4 017918 888381
Pack	1
Customs tariff	85366990
Catalog page information	Page 46 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
2006-03-21



Technical data

General data


Rated current at 40°C	4 A
Rated voltage	250 V
Number of positions	4
Volume resistance	$\leq 8 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Ambient temperature (operation)	-40 °C ... 85 °C (Male connector / female connector)

General characteristics

Standards/regulations	M12 connector IEC 61076-2-101
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuZn
Contact surface material	CuSnZn
Contact carrier material	PA 66
Material of grip body	PBT
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	NBR
Type of connection	Screw connection
Conductor cross section stranded min.	0.25 mm ²
Conductor cross section stranded max.	0.75 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	18
External cable diameter	3 mm ... 5.2 mm (2x)
Status display	No


Drawings

Dimensioned drawing




M12 x 1 male connector, straight

Schematic diagram



Male/Female M12



Cable connection side M12 (screw connection)

Pin assignment M12 plug, 4-pos., A-coded, view plug side

