

# SAC-8P- 5,0-PUR/M12FS SH

Order No.: 1522888



Sensor/Actuator cable, 8-position, PUR, halogen-free, Black-gray RAL 7021, shielded, Free conductor end, on Socket, straight M12, A-coded, Cable length: 5 m

## Commercial data

|                          |                                                                                                       |
|--------------------------|-------------------------------------------------------------------------------------------------------|
| EAN                      | <br>4 017918 957667 |
| Pack                     | 30                                                                                                    |
| Customs tariff           | 85444290                                                                                              |
| Catalog page information | Page 95 (PC-2009)                                                                                     |

## Product notes

WEEE/RoHS-compliant since:  
2006-11-08



## Technical data

### General data

|                       |                            |
|-----------------------|----------------------------|
| Rated current at 40°C | 2 A                        |
| Rated voltage         | 30 V                       |
| Number of positions   | 8                          |
| Volume resistance     | $\leq 5 \text{ m}\Omega$   |
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Length of cable       | 5 m                        |

|                                            |                                                      |
|--------------------------------------------|------------------------------------------------------|
| Stripping length of the free conductor end | 50 mm                                                |
| Ambient temperature (operation)            | -25 °C ... 90 °C (Male connector / female connector) |

**General characteristics**

|                             |                                             |
|-----------------------------|---------------------------------------------|
| Standards/regulations       | M12 connector IEC 61076-2-101               |
| Coding                      | A - standard                                |
| Surge voltage category      | II                                          |
| Pollution degree            | 3                                           |
| Degree of protection        | IP65/IP67/IP69K                             |
| Insertion/withdrawal cycles | ≥ 100                                       |
| Contact material            | CuZn                                        |
| Contact surface material    | Ni/Au                                       |
| Contact carrier material    | TPU GF                                      |
| Material of grip body       | TPU, hardly inflammable, self-extinguishing |
| Material, knurls            | Zinc die-cast, (nickel-plated)              |
| Sealing material            | NBR                                         |
| Status display              | No                                          |

**Conductor data**

|                                    |                                                    |
|------------------------------------|----------------------------------------------------|
| Cable type                         | PUR halogen-free black                             |
| Cable type (abbreviation)          | PUR                                                |
| Cable abbreviation                 | Li9YVI-C-VI-11Y                                    |
| Conductor cross section            | 0.25 mm <sup>2</sup>                               |
| AWG signal line                    | 24                                                 |
| Conductor structure signal line    | 32 x 0.10 mm                                       |
| Core diameter including insulation | 1.17 mm ±0.02 mm                                   |
| Thickness, insulation              | ≥ 0.21 mm (Core insulation)                        |
|                                    | Approx. 0.6 mm (Outer cable sheath)                |
| External cable diameter            | 5.9 mm ±0.15 mm                                    |
| Wire colors                        | Brown, white, green, yellow, gray, pink, blue, red |
| External sheath, color             | Black-gray RAL 7021                                |
| Insulation resistance              | ≥ 100 MΩ*km (at 20°C)                              |
| Conductor resistance               | max. 78 Ω/km (at 20°C)                             |
| Nominal voltage, conductor         | ≤ 300 V                                            |
| Test voltage, conductor            | ≥ 3000 V                                           |
| Overall twist                      | 8 wires around filler to the core                  |

|                                               |                                                                     |
|-----------------------------------------------|---------------------------------------------------------------------|
| Shielding                                     | Tinned copper braided shield                                        |
| Optical shield covering                       | 85 %                                                                |
| Outer sheath, material                        | PUR                                                                 |
| Material, filler                              | PE                                                                  |
| Material conductor insulation                 | PP                                                                  |
| Conductor material                            | Bare Cu litz wires                                                  |
| Cable weight                                  | 54 kg/km                                                            |
| Smallest bending radius, fixed installation   | 59 mm                                                               |
| Smallest bending radius, movable installation | 59 mm                                                               |
| Number of bending cycles                      | 4000000                                                             |
| Bending radius                                | 59 mm                                                               |
| Traversing path                               | 10 m                                                                |
| Traversing rate                               | 3 m/s                                                               |
| Acceleration                                  | 10 m/s <sup>2</sup>                                                 |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)                        |
|                                               | -5 °C ... 80 °C (cable, flexible installation)                      |
| Special properties                            | Flexible cable conduit capable                                      |
|                                               | Silicone-free                                                       |
|                                               | Free of substances which would hinder coating with paint or varnish |
| Flame resistance                              | in accordance with DIN UL-Style 20549                               |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815                            |
| Resistance to oil                             | in accordance with DIN EN 60811-2-1                                 |
| Other resistance                              | Highly resistant to acids, alkaline solutions and solvents          |
|                                               | hydrolysis and microbe resistant                                    |

## Certificates




Certification

CUL Listed, UL Listed


## Drawings

### Dimensioned drawing




M12 x 1 female connector, straight, shielded

### Circuit diagram



Contact assignment of the M12 socket

### Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side