

SAC-3P-MS-FS SCO/.../...

Order No.: 1523544



Sensor/Actuator cable, 3-position, Plug, straight M12-SPEEDCON, A-coded, on Socket, straight M12-SPEEDCON, A-coded, Cable length: Free input (0.2 ... 40.0 m)



Commercial data	
Note	Made-to-order
Pack	1
Customs tariff	85444290
Catalog page information	Page 74 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
2006-07-12



Technical data

General data	
Rated current at 40°C	4 A
Rated voltage	250 V
Number of positions	3
Volume resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Length of cable	Free input (0.2 ... 40.0 m)

General characteristics

Standards/regulations	M12 connector IEC 61076-2-101
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP65/IP68/IP69K
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	NBR
Status display	No
Test voltage	2500 V

Line characteristics

Note	This order comprises a cable with a freely selectable cable type. As a result, technical data about the cable types available for selection is not displayed here. This information is available on request.
------	--

Certificates

Certification

CUL Listed, UL Listed


Configuration options

Cable type


PUR halogen-free black [PUR]
 PVC black [PVC]
 PUR/PVC gray [100]
 PUR/PVC orange [110]
 PUR/PVC yellow [140]
 PUR irradi. halogen-free orange [150]
 PUR halogen-free orange [180]
 PUR halogen-free gray [280]
 PVC gray [500]
 PVC yellow [540]
 PVC yellow 105 °C [542]
 PUR highflex gray [800]

Drawings

Dimensioned drawing




M12 x 1 male connector, straight




M12 x 1 female connector, straight

Circuit diagram




Contact assignment of the M12 plug and the M12 socket

Schematic diagram



Pin assignment M12 plug, 3-pos., A-coded, view male side



Pin assignment M12 socket, 3-pos., A-coded, view female side