

SAC-8P-MS-FR SH SCO/.../...

Order No.: 1523939



Sensor/Actuator cable, 8-position, shielded, Plug, straight M12-SPEEDCON, A-coded, on Socket, angled M12-SPEEDCON, A-coded, Cable length: Free input (0.2 ... 40.0 m)



Product notes

WEEE/RoHS-compliant since:
2005-06-01



Commercial data

Note	Made-to-order
Pack	1
Customs tariff	85444290
Catalog page information	Page 94 (PC-2009)

Technical data

General data

Rated current at 40°C	2 A
Rated voltage	30 V
Number of positions	8
Volume resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Length of cable	Free input (0.2 ... 40.0 m)

General characteristics

Standards/regulations	M12 connector IEC 61076-2-101
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP65/IP67/IP69K
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	NBR
Status display	No

Line characteristics

Note	This order comprises a cable with a freely selectable cable type. As a result, technical data about the cable types available for selection is not displayed here. This information is available on request.
------	--

Certificates

Certification


CUL Listed, UL Listed

Configuration options


Cable type	PUR halogen-free black [PUR] PVC black [PVC] PUR halogen-free gray [280]
------------	--

Drawings

Dimensioned drawing




M12 x 1 male connector, straight, shielded




M12 x 1 female connector, angled, shielded

Circuit diagram




Contact assignment of the M12 plug and the M12 socket

Schematic diagram



Pin assignment M12 plug, 8-pos., view
plug side



Pin assignment M12 socket, 8-pos., A-
coded, view female side