

SACC-EC-M12FSB-5CON-M16/0,5

This product has been replaced by a newer version.

Order No.: 1528471



Sensor/Actuator flush-type socket, 5-pos., M12, B-coded, front/screw mounting with M16 thread, can be positioned, with 0.5 m TPE litz wire, 5 x 0.34 mm²

Commercial data

EAN	 4 046356 023405
Note	Made-to-order
Pack	1
Customs tariff	85366990
Catalog page information	Page 19 (PC-2007)

Product notes

WEEE/RoHS-compliant since:
2006-03-10



Technical data

General data

Rated current at 40°C	4 A
Rated voltage	60 V
Number of positions	5
Volume resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ

Length of cable	0.5 m
-----------------	-------

General characteristics

Coding	B - inverse
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA66 GF
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	NBR
Type of connection	Individual wires
Status display	No

Conductor data


Cable type	TPE litz wire
Conductor cross section	0.25 mm ²
AWG signal line	22
Conductor structure signal line	7x 0.25 mm
Core diameter including insulation	1.2 mm ±0.07 mm
Thickness, insulation	0.21 mm (Core insulation)
Wire colors	Black, brown, blue, white, gray
Nominal voltage, conductor	300 V
Test voltage, conductor	2000 V AC
Material conductor insulation	TPE
Conductor material	Tin-plated Cu litz wires

Accessories


Item	Designation	Description
Assembly		
1504097	SACC-E-MU-M16	Flat nut with M16 thread

Drawings

Dimensioned drawing




M12 flush-type connector




Housing cutout for M16 fastening thread,
mounting panel with thread

Circuit diagram



Contact assignment of the M12 plug and the M12 socket

Schematic diagram



Pin assignment M12 female connector, 5-pos., B-coded, female
side