

SAC-4P-MS-M8FR-2L SCO/.../...

Order No.: 1535723



Sensor/Actuator cable, 4-position, Plug, straight M12-SPEEDCON, A-coded, on Socket, angled M8, with 2 LEDs, Cable length: Free input (0.2 ... 40.0 m)



Commercial data

Note	Made-to-order
Pack	1
Customs tariff	85444290
Catalog page information	Page 80 (PC-2009)

Technical data

General data

Rated current at 40°C	4 A
Rated voltage	24 V
Number of positions	4
Volume resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Length of cable	Free input (0.2 ... 40.0 m)

General characteristics

Standards/regulations	M12 connector IEC 61076-2-101
Coding	A - standard
Surge voltage category	II
Pollution degree	3

Degree of protection	IP65/IP68/IP69K
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	NBR
Status display	2 LEDs

Line characteristics

Note	This order comprises a cable with a freely selectable cable type. As a result, technical data about the cable types available for selection is not displayed here. This information is available on request.
------	--

Certificates

Certification


CUL Listed, UL Listed

Configuration options


Cable type	PUR halogen-free black [PUR] PVC black [PVC] PUR/PVC gray [100] PUR/PVC yellow [140] PUR halogen-free orange [180] PVC gray [500] PUR highflex gray [800]
------------	---

Drawings

Dimensioned drawing




M12 x 1 male connector, straight




Socket M8 x 1, angled, with LED

Circuit diagram




Contact assignment of M12 plugs / M8 sockets

Schematic diagram



Pin assignment M12 plug, 4-pos., A-coded, view plug side



Pin assignment M8 socket, 4-pos., view female side