

SAC-8P-100,0-PVC/SH-0,25

Order No.: 1550708



Cable ring, PVC, black, 8-pos. shielded, conductor colors: White / brown / green / yellow / gray / pink / blue / red, cable length: 100 m

Commercial data

EAN	 4 046356 170512
Note	Made-to-order
Pack	1
Customs tariff	85444995
Catalog page information	Page 134 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
2006-11-10



Technical data

General data

Number of positions	8
Length of cable	100 m

Conductor data

Cable type	PVC shielded black
Cable abbreviation	LiYF-C-Y

Conductor cross section	0.25 mm ²
	0.227 mm ² (Drain wire)
AWG signal line	24
Conductor structure signal line	32 x 0.10 mm
Core diameter including insulation	1.2 mm ±0.02 mm
Thickness, insulation	≥ 0.23 mm (Core insulation)
	≥ (Outer cable sheath)
External cable diameter	6.10 mm
Wire colors	Brown, white, green, yellow, gray, pink, blue, red
External sheath, color	Black RAL 9005
Insulation resistance	≥ 1 GΩ*km
Conductor resistance	≤ 78 Ω/km
Nominal voltage, conductor	300 V
Test voltage, conductor	2500 V
Overall twist	8 wires around filler to the core
Shielding	Braided copper wires
Optical shield covering	85 %
Outer sheath, material	PVC
Material, filler	PVC
Material conductor insulation	PVC
Conductor material	Bare Cu litz wires
Cable weight	64 kg/km
Ambient temperature (operation)	-25 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 80 °C (cable, flexible installation)

Certificates



Certification

CUL Listed, UL Listed

Accessories

Item	Designation	Description
------	-------------	-------------

Tools

1212623	WIREFOX SAC	Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length
---------	-------------	--