

SACC-M 8MR-4CON-M

Order No.: 1554209



Sensor/actuator connector, angled, 4-pos., M8, solder connection, cable diameter max. 5 mm

Commercial data

EAN	 4 046356 161756
Pack	1
Customs tariff	85444290
Catalog page information	Page 40 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
2006-10-05



Technical data

General data

Rated current at 40°C	4 A
Rated voltage	30 V
Number of positions	4
Volume resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$

General characteristics

Standards/regulations	M8 connector IEC 61076-2-104
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PUR / PA66
Material of grip body	PBT
Material, knurls	Nickel-plated brass
Sealing material	NBR
Type of connection	Solder cup
Conductor cross section stranded min.	0.08 mm ²
Conductor cross section stranded max.	0.34 mm ²
Conductor cross section AWG/kcmil min.	28
Conductor cross section AWG/kcmil max	22
External cable diameter	3.5 mm ... 5 mm
Status display	No


Accessories

Item	Designation	Description
General		
1436945	SACC-M 8-SET/2,2-3,5	Sensor/actuator connector, accessories, pressure screw and seal, for unshielded M8 connector, cable diameter 2.2 mm - 3.5 mm

Drawings

Dimensioned drawing

M8 x 1 male connector, angled version



Schematic diagram

Pin assignment M8 plug, 4-pos., view male side

