

SACC-MINMS-5CON-PG16

Order No.: 1559039



Sensor/actuator plug, plug, straight, 5-pos., 7-8", screw connection, metal knurl, cable gland Pg16

Commercial data

EAN	 4 046356 299985
Pack	1
Customs tariff	85444290
Catalog page information	Page 53 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
2007-06-19



Technical data

General data


Rated current at 40°C	9 A
Rated voltage	250 V
Number of positions	5
Volume resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Ambient temperature (operation)	-25 °C ... 85 °C (Male connector / female connector)

General characteristics


Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PUR / PA66
Material of grip body	PBT
Material, knurls	Zinc die-cast, (nickel-plated)
Type of connection	Screw connection
Conductor cross section stranded min.	0.34 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	22
Conductor cross section AWG/kcmil max	16
External cable diameter	12 mm ... 14 mm
Status display	No

Drawings

Functional drawing



Dimensioned drawing



Plug 7/8"-16UNF, straight, Pg16

Schematic diagram

Pin assignment, plug, 7/8"-16UNF, 5-pos., view of male side

