




Model Number


V3-WM-5M-PUR-V11-G

Connection cable, M8 to M12, PUR cable, 3-pole

Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold plated contacts
- Halogen-free
- Suitable for 2- and 3-wire technology

Dimensions



Technical data

General specifications

Number of poles	3
Connection 1	Connector, female
Construction type 1	angled
Threading 1	M8
Connection 2	Connector, male
Construction type 2	straight
Threading 2	M12

Electrical specifications

Operating voltage	max. 60 V DC
Test voltage	> 1500 V _{eff} AC
Operating current	max. 3 A
Volume resistance	< 5 mΩ

Ambient conditions

Ambient temperature	-25 ... 100 °C (248 ... 373 K) for temperatures over 80 °C (353 K) reduced elongation at tear
Degree of soiling	3

Mechanical specifications

Contact elements	spring-loaded contact socket
pin diameter	1 mm
Protection degree	IP68
Material	
Contacts	CuSn / Au
Contact surface	Au
Handle	TPU, green
Cable	PUR
Slotted nut	diecast zinc
(Cap??-translator) connector	diecast zinc
Core isolation	PP
Cable	fine-strand, flexible
Sheath diameter	Ø4.8 mm
Bend radius	> 10 x conductor diameter, appropriate for conveyor chains
Colour	grey
Cores	3 x 0.34 mm ²
Conductor construction	19 x 0.15 mm Ø
Length	L 5 m
Flammability	
Contact material	94V-2
Housing	94V-2

Electrical connection 1



Electrical connection 2

