




Model number
V1-W-5M-PUR-ABG-V1-W

Connecting cable, M12 to M12, PUR
cable 4-pin, shielded

- Features**
- Knurled nut suitable for tool assembly
 - Immunity to vibration, with mechanical latching
 - Screen put on the slotted nut
 - Gold plated contacts
 - Protection degree IP67 / IP68 / IP69K
 - Halogen-free
 - Suitable for 2-, 3- and 4-wire technology


Dimensions



Technical data

General specifications	
Number of poles	4 + shield
Connection 1	Connector, female
Construction type 1	angled
Threading 1	M12
Connection 2	Connector, male
Construction type 2	angled
Threading 2	M12
Electrical specifications	
Operating voltage	max. 300 V DC
Test voltage	> 1500 V _{eff} AC
Operating current	max. 4 A
Volume resistance	< 5 mΩ
Ambient conditions	
Ambient temperature	-25 ... 100 °C (248 ... 373 K) for temperatures over 80 °C (353 K) reduced elongation at tear
Degree of soiling	3
Mechanical specifications	
Contact elements	spring-loaded contact socket
pin diameter	1 mm
Protection degree	IP67 / IP68 / IP69K
Material	
Contacts	CuSn / Au
Contact surface	Au
Handle	TPU, green
Cable	PUR
Slotted nut	diecast zinc
(Cap??-translator) connector	diecast zinc
Core isolation	PP
Cable	fine-strand, flexible
Sheath diameter	Ø4.8 mm
Bend radius	> 10 x conductor diameter, appropriate for conveyor chains
Colour	grey
Cores	4 x 0.34 mm ²
Conductor construction	19 x 0.15 mm Ø
Shield	Braid
Length	L 5 m
Flammability	
Contact material	94V-2
Housing	94V-2

Electrical connection 1



Electrical connection 2

