

SENSOTRONIK

The image shows a cable assembly with a green connector and a black cable. The cable has four conductors (two blue, two brown) and a green outer jacket. The connector is a green plastic housing with a metal pin. The cable is shown in two positions, one slightly behind the other, to show its flexibility.



SAC-3P-M12Y/.../M12FS B

givarkabel för 2 givare M 12



SAC-3P-M12Y/.../M12FR B

givarkabel, vinklad, för 2 givare M 12




SAC-3P-M12Y/.../M12FR-2L B

givarkabel, vinklad, för 2 givare M 12, med 2 LEDs


Typ	Artikel-nr.	st. förp.
SAC-3P-M12Y/2X0,3-PUR/M12FS B SAC-3P-M12Y/2X0,6-PUR/M12FS B SAC-3P-M12Y/2X1,5-PUR/M12FS B SAC-3P-M12Y/2X3,0-PUR/M12FS B SAC-3P-M12Y-2XM12FS B/.../...	16 68 95 9 16 68 96 2 16 68 97 5 16 68 98 8 16 97 36 0/...	1
4 320 ≤ 5 – 30 till + 80 / – 5 till + 70 – 25 till + 90		
4 (3)		
0,34 (42 x 0,1 mm)		
5,2		
CuSn // Ni / Au		
TPU, svårantändlig, självslocknande		
IP 67		

Typ	Artikel-nr.	st. förp.
SAC-3P-M12Y/2X0,3-PUR/M12FR B SAC-3P-M12Y/2X0,6-PUR/M12FR B SAC-3P-M12Y/2X1,5-PUR/M12FR B SAC-3P-M12Y/2X3,0-PUR/M12FR B SAC-3P-M12Y-2XM12FR B/.../...	16 68 99 1 16 69 00 0 16 69 01 3 16 69 02 6 16 97 37 3/...	1
4 320 ≤ 5 – 30 till + 80 / – 5 till + 70 – 25 till + 90		
4 (3)		
0,34 (42 x 0,1 mm)		
5,2		
CuSn // Ni / Au		
TPU, svårantändlig, självslocknande		
IP 67		


Typ	Artikel-nr.	st. förp.
SAC-3P-M12Y/2X0,3-PUR/M12FR-2L B SAC-3P-M12Y/2X0,6-PUR/M12FR-2L B SAC-3P-M12Y/2X1,5-PUR/M12FR-2L B SAC-3P-M12Y/2X3,0-PUR/M12FR-2L B SAC-3P-M12Y-2XM12FR-2L B/.../...	16 69 03 9 16 69 04 2 16 69 05 5 16 69 06 8 16 97 38 6/...	1
4 24 DC ≤ 5 – 30 till + 80 / – 5 till + 70 – 25 till + 90		
4 (3)		
0,34 (42 x 0,1 mm)		
5,2		
CuSn // Ni / Au		
TPU, svårantändlig, självslocknande		
IP 67		




Y-kontakt M 12 x 1



Hona M 12 x 1, rakt utförande



Hona M 12 x 1, vinklat utförande



Hona M 12 x 1, vinklat utförande med LED



SAC-3P-M12Y/.../M 8FR

givarkabel, vinklad, för 2 givare M 8



SAC-3P-M12Y/.../M 8FR-2L

givarkabel, vinklad, för 2 givare M 8, med 2 LEDs

Typ	Artikel-nr.	st. förp.
SAC-3P-M12Y/2X0,3-PUR/M 8FR SAC-3P-M12Y/2X0,6-PUR/M 8FR SAC-3P-M12Y/2X1,5-PUR/M 8FR SAC-3P-M12Y/2X3,0-PUR/M 8FR SAC-3P-M12Y-2XM 8FR/.../...	16 71 37 3 16 71 38 6 16 71 39 9 16 71 40 9 16 97 40 9/...	1
4 100 ≤ 5 – 30 till + 80 / – 5 till + 70 – 25 till + 90 4 (3) 0,25 (32 x 0,1 mm) 4,4 CuSn // Ni / Au TPU, svårantändlig, självslocknande IP 67		

Typ	Artikel-nr.	st. förp.
SAC-3P-M12Y/2X0,3-PUR/M 8FR-2L SAC-3P-M12Y/2X0,6-PUR/M 8FR-2L SAC-3P-M12Y/2X1,5-PUR/M 8FR-2L SAC-3P-M12Y/2X3,0-PUR/M 8FR-2L SAC-3P-M12Y-2XM 8FR-2L/.../...	16 71 41 2 16 71 42 5 16 71 43 8 16 71 44 1 16 97 41 2/...	1
4 24 DC ≤ 5 – 30 till + 80 / – 5 till + 70 – 25 till + 90 4 (3) 0,25 (32 x 0,1 mm) 4,4 CuSn // Ni / Au TPU, svårantändlig, självslocknande IP 67		

