

M12 male straight / MSUD valve form A 18mm PUR/PVC-JB 5x0,34 black 0,3m

Form A (18 mm) ? M12, male straight
for pressure switches
LED (red/green)
5-pole

Image



Vicarious picture

Approvals



Form

Technical Data

Operating voltage	24 V DC $\pm 25\%$
Operating current per contact (40 °C)	max. 4 A
Housing	Plastic, black (gray on request)
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)
Temperature range	-25...+85 °C, depending on cable quality

Cable

No./diameter of wires	5 \times 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk, gnye)
C-track properties	2 Mio.
Jacket	PUR/PVC
Outer diameter	approx. 5.9 mm
Bend radius (mobile)	15 \times outer diameter
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+80 °C

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 04/13

Commercial data

Net weight	61
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1


Comments

Further cable lengths on request.

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Contact layout



Circuit diagram

