


Proximity Sensors Inductive ABS Housing Type DU, Fork-shaped



- Fork-shaped ABS housing
- Slot sizes: 3.5, 5, 6, 10 mm
- Power supply: 8.2 VDC (Namur)
24 VDC
- Output: Namur (DIN 19234)
Transistor NPN, make switching
- Protection: Reverse polarity
- 2 m cable

Product Description

Special fork-shaped proximity switch. Slot sizes 3.5, 5.6 or 10 mm. With transistor NPN or made in accordance with Namur DIN 19234. Sturdy ABS housing.

Ordering Key

DU 10 E

Type: Inductive proximity switch

Slot size

Output type

Type Selection

Slot size mm	Ordering no. Namur	Ordering no. Transistor NPN Make switching
3.5	DU 3.5	
5	DU 5	
6	DU 6	DU 6 E
10	DU 10	DU 10 E

Specifications


	Namur	Transistor NPN
Rated operational volt. (U_e) (U_B)	8.2 VDC 7 to 9 VDC (6 to 35 VDC, all specifications not observed in extended supply range)	24 VDC 21.6 to 26.4 VDC (ripple incl.)
Self-inductance	$\leq 500 \mu H$	
Self-capacitance	$\leq 120 nF$	
Ripple		$\leq 10\%$
Rated operational current (I_e)		$\leq 200 mA$
No-load supply current (I_o)	Activated: $\leq 1 mA$ Not activated: $\geq 3 mA$ Max.: 9.35 mA	$\leq 15 mA$
Voltage drop (U_d)		DU 6 E $\leq 2.0 V$ at max. load DU 10 E $\leq 1.0 V$ at max. load
Protection	None	Reverse polarity
Transient voltage	$\leq 1 kV/0.5 J$ (prepared)	$\leq 1 kV/0.5 J$ (prepared)
Power ON delay	None	None
Frequency of operating cycles (f)	DU 3.5 2000 Hz DU 5 1500 Hz	DU 6 E 2000 Hz DU 10 E 1000 Hz
Size of test object (height x length x width)	DU 3.5 10 x 10 x 0.5 mm DU 5 10 x 10 x 0.5 mm DU 6 16 x 16 x 1 mm DU 10 16 x 20 x 1 mm	DU 6 E 16 x 16 x 1 mm DU 10 E 16 x 20 x 1 mm

Specifications (cont.)


	Namur	Transistor NPN
Repeat accuracy (R)	≤ 10%	≤ 10%
Effective operating dist. (S _r)	$0.9 \times S_n \leq S_r \leq 1.1 \times S_n$	$0.9 \times S_n \leq S_r \leq 1.1 \times S_n$
Usable operating dist. (S _u)	$0.8 \times S_r \leq S_u \leq 1.2 \times S_r$	$0.8 \times S_r \leq S_u \leq 1.2 \times S_r$
Ambient temperature		
Operating	-20° to +60°C (-4° to +140°F)	-20° to +60°C (-4° to +140°F)
Storage	-25° to +70°C (-13° to +158°F)	-25° to +70°C (-13° to +158°F)
Degree of protection	IP 67 (Nema 1, 3, 4, 6, 13)	IP 67 (Nema 1, 3, 4, 6, 13)
Housing material	Blue ABS	Blue ABS
Cable	DU 3.5 2 m, 2 x 0.1 mm ² (2 wires) DU 5 2 m, 2 x 0.1 mm ² (2 wires) DU 6 2 m, 2 x 0.25 mm ² DU 10 2 m, 2 x 0.25 mm ² grey PVC, oil proof	DU 6 E 2 m, 3 x 0.25 mm ² DU 10 E 2 m, 3 x 0.25 mm ² grey PVC, oil proof
Weight (cable included)	DU 3.5 17 g DU 6 72 g DU 5 17 g DU 10 116 g	DU 6 E 72 g DU 10 E 116 g
CE-marking	Yes	

Dimensions

Type	U mm	L mm	H mm	W mm	A mm	B Ø mm	C mm	D mm	E mm	F mm	G mm	I mm	J mm	K mm	M mm	N mm	O Ø mm	P Ø mm
DU 3.5	3.5	15	19.2	10.2	5	2	10.5	6.85	17	10	5	Ø 1.1	2	2000	1			
DU 5	5	15	19.2	10.2	5	2	9	6.85	17	10	5	Ø 1.1	2	2000	1			
DU 6	6	30	26.8	16.4	10	2.3	10.1	20	10	11	15.25	2.2	17	2000	9	12.5	6.5	4.2
DU 10	10	45	44.5	25.6	17	4.5	17	32	13	15	20	2.95	24	2000	10	20	8.5	4.1



DU 3.5 - DU 5



DU 6 - DU 10

Wiring Diagrams

Refer to "Wiring Diagrams", Technical Information.

Power Supplies

Power supplies VAC: > SS 110.
 Power supplies VDC: > SS 130/140.

Installation Hints

Refer to "Installation Hints", Technical Information.

Namur, Amplifier Relay

> SD 110/210.
 > SD 170/270. Refer to Technical Information.