



My-Com precision switches

		My-Com A	My-Com B / My-Com BS
			
activating force	30 grams / cN	1502-001 My-Com A30/80	1502-009 My-Com B30/80
	50 grams / cN	1502-003 My-Com A50/80	1502-011 My-Com B50/80
	75 grams / cN	1502-005 My-Com A75/80	1502-013 My-Com B75/80
	100 grams / cN	1502-007 My-Com A100/80	1502-015 My-Com B100/80
electrical data	max. AC voltage	24 VAC	24 VAC
	max. switch. current AC	50 mA	50 mA
	max. DC voltage	15 VDC	15 VDC
	max. switch. current DC	2 mA	2 mA
activating force	NPN 75 grams		
	PNP 75 grams		
electrical data	max. supply voltage		
	max. load current at 24 VDC		
	min. load resistance		
	output		
contact		zirconium oxide ZrO ₂	zirconium oxide ZrO ₂
housing		brass nickel plated	brass nickel plated
special features		protection class IP 50	protection class IP 50
connection diagram / output function		 normally closed (NC) / break function	 normally closed (NC) / break function
options		for connector base version add .../S35 * length with connector base S35 approximately 30 mm	for connector base version add My-Com BSxx
		overrun 1,5 mm approx.	overrun 1,5 mm approx.
		